

200.33234

In	R ±2%
13A	1,5kΩ 0,5W
20A	680Ω 0,5W
32A	220Ω 0,5W

PP CP

N L1

L3 L2

R

max 102 mm

A

0,75mm<sup>2</sup>  
L=100mm

0,8Nm

0,8Nm

(\*) SCREW TERMINALS

SUGGESTION FOR CABLE

Type: S05BQ-F or equivalent

Core insulation:  
EPR-rubber, crosslinked, type E16

Outer sheath:  
PUR, type TMRU flame-retardant

Operating temperature:  
-40°C to +90°C

InfoTECH

ITALY WORLDWIDE

Numero Verde 800-018009 ScameOnLine  
www.scame.com infotech@scame.com

MP39055

ZP90876-1

Serie LIBERA

SCAME

200.33234

In	R ±2%
13A	1,5kΩ 0,5W
20A	680Ω 0,5W
32A	220Ω 0,5W

PP CP

N L1

L3 L2

R

max 102 mm

A

0,75mm<sup>2</sup>  
L=100mm

0,8Nm

0,8Nm

(\*) SCREW TERMINALS

SUGGESTION FOR CABLE

Type: S05BQ-F or equivalent

Core insulation:  
EPR-rubber, crosslinked, type E16

Outer sheath:  
PUR, type TMRU flame-retardant

Operating temperature:  
-40°C to +90°C

InfoTECH

ITALY WORLDWIDE

Numero Verde 800-018009 ScameOnLine  
www.scame.com infotech@scame.com

MP39055

ZP90876-1

Serie LIBERA

SCAME

200.33234

In	R ±2%
13A	1,5kΩ 0,5W
20A	680Ω 0,5W
32A	220Ω 0,5W

PP CP

N L1

L3 L2

R

max 102 mm

A

0,75mm<sup>2</sup>  
L=100mm

0,8Nm

0,8Nm

(\*) SCREW TERMINALS

SUGGESTION FOR CABLE

Type: S05BQ-F or equivalent

Core insulation:  
EPR-rubber, crosslinked, type E16

Outer sheath:  
PUR, type TMRU flame-retardant

Operating temperature:  
-40°C to +90°C

InfoTECH

ITALY WORLDWIDE

Numero Verde 800-018009 ScameOnLine  
www.scame.com infotech@scame.com

MP39055

ZP90876-1

Serie LIBERA

SCAME

200.33234

In	R ±2%
13A	1,5kΩ 0,5W
20A	680Ω 0,5W
32A	220Ω 0,5W

PP CP

N L1

L3 L2

R

max 102 mm

A

0,75mm<sup>2</sup>  
L=100mm

0,8Nm

0,8Nm

(\*) SCREW TERMINALS

SUGGESTION FOR CABLE

Type: S05BQ-F or equivalent

Core insulation:  
EPR-rubber, crosslinked, type E16

Outer sheath:  
PUR, type TMRU flame-retardant

Operating temperature:  
-40°C to +90°C

InfoTECH

ITALY WORLDWIDE

Numero Verde 800-018009 ScameOnLine  
www.scame.com infotech@scame.com

MP39055

ZP90876-1